JC20 Rac'd PCT/PTO 1 9 MAR 2002

US DI PARTMENI OF COMMERCE, PATI NI AND TRADEMARK OFFI

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371

ÄTTÖRNEY'S DOCKET NÜMBER 33942R003

U S APPLICATION NO. (if known,

*****1**07*088233

INTERNATIONAL APPLICATION NO. PCT/BR00/00105	INTERNATIONAL FILING DATE September 20, 2000	PRIORITY DATE CLAIMED September 20, 1999
--	---	---

TITLE OF INVENTION	A METHOD FOR CONTROLLING AND PROTECTING ELECTRIC MOTORS, A SYSTEM FOR
	CONTROLLING ELECTRIC MOTORS AND AN ELECTRIC MOTOR SYSTEM
APPLICANT(S) FOR DO/EO/US	Paulo Sergio Dainez; Luiz Von Dokonal and Marcos Guilherme Schwarz.

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

- This is a FIRST submission of items concerning a filing under 35 U S.C 371
- 2. This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U S C. 371.
- 3.

 This express request to begin national examination procedures (35 U.S.C. 371(f) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(l).
- 4.

 A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
- - a.

 is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. □ has been transmitted by the International Bureau (see accompanying PCT Form 308).
 - c. \square is not required, as the application was filed in the United States Receiving Office (RO/US).
- 6. □ A translation of the International Application into English (35 U.S.C. 371(c)(2))
- 7.

 ✓ Amendments to the claims of the International Application under PCT Article 34 (35 U.S.C. 371).
 - a. \square are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. $\hfill\Box$ have been transmitted by the International Bureau
 - $c. \square$ have not been made, however, the time limit for making such amendments has NOT expired.
 - $d. \bowtie have not been made and will not be made.$
- 8.

 A translation of the amendments to the claims under PCT Article 34 (35 U.S C 371)
- 9. □ An oath or declaration of the inventor(s) (35 U.S.C 371(c)(4))
- 10.

 A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U S.C. 371(c)(5)).

Items 11. to 16. below concern other document(s) or information included:

- 11.

 An Information Disclosure Statement under 37 CFR 1 97 and 1 98
- 12.

 An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
- - ☐ A SECOND or SUBSEQUENT preliminary amendment.
- 14. □ A substitute specification.
- 15. A change of power of attorney and/or address letter.
- 16.

 ✓ Other items or information:
- a. PCT Publication WO 01/22566 with International Search Report (PCT/ISA/210)
- b. PCT Request (Form PCT/RO/101)
- c. Notification of Transmittal of the International Search Report or the Declaration (Form PCT/ISA/220)
- d. International Preliminary Examination Report (Form PCT/IPEA/409 and PCT/IPEA/416)
- e. PCT Demand (Form PCT/IPEA/401)

PATENT TRADEMARK OFFICE

4

US DI PARTMENT OF COMMERCE, PATENT AND TRADEMARK OTFICE ATTORNEYS DOCKET NUMBER 2002

E UNITED STATES

JC18 Record CT/PTO 1 9 MAR 2002

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371

U.S APPLICATION NO (if known, see $\frac{37 \text{ CFR 1.5}}{10/088233}$

		* 	·			
17. ™ The following fees as	e submitted.			CALCULATIONS	PTO USE ONLY	
Basic National Fee (3' Search Report has been						
International preliminar (37 CFR 1 482)						
No international prelim paid to USPTO (37 CF						
Neither international pr international search fee						
	y examination fee paid to USPT provisions of PCT Article 33(2)		\$100.00			
		NTER APPROPRIATE B.	ASIC FEE AMOUNT =	\$890 00	,	
Surcharge of \$130.00 for fur priority date (37 CFR 1.495)	rnishing the oath or declaration l			\$		
Claims	Number Filed	Number Extra	Rate			
Total Claims	7 - 20 =	0	x \$18 00			
Independent Claims	3 -3 =	0	x \$84.00			
Multiple dependent claim(s)	(if applicable)		+ \$280 00	.00	_	
		TOTAL OF ABOV	E CALCULATIONS =	\$ 890.00		
Reduction by ½ for filing by 37 CFR 1 9, 1.27, 1.28).	\$.00					
			SUBTOTAL =	\$ 890.00		
Processing fee of \$130.00 for claimed priority date (37 CF						
TOTAL NATIONAL FEE =				.890.00		
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				\$ 00	÷	
		ТОТА	L FEES ENCLOSED =	\$890.00		
				Amount to be refunded	\$	
				charged	\$	
a. A check in the amount of \$890.00 to cover the above fees is enclosed.						
b. Please charge my Deposit Account No in the amount of \$ to cover the above fees.						
c. B The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No 02-4300.						
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.						
SEND ALL CORRESPON			. 1			
SMITH, GAMBRELL & RUSSELL, LLP						
1850 M Street, N.W., Washington, D.C. 200	SIGNATUR	E				
Telephone: (202) 659-	elephone: (202) 659-2811 Dennis C. Rodgers, Reg. No. 32,9					
Facsimile: (202) 263-4329 NAME REGISTRATION N Date: <u>March 19, 20</u>						

33942R003

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s): Paulo Sergio Dainez, et al.

International Application No.: PCT/BR00/00105

International Filing Date: September 20, 2000

U.S. Serial No.: To Be Assigned

Group Art Unit: To Be Assigned

Filed: : March 19, 2002 (Herewith)

Examiner: To Be Assigned

For:

A METHOD FOR CONTROLLING AND PROTECTING ELECTRIC MOTORS, A SYSTEM FOR CONTROLLING ELECTRIC MOTORS AND AN ELECTRIC

MOTOR SYSTEM

PRELIMINARY AMENDMENT

Commissioner for Patents Washington, D.C. 20231

Sir:

Prior to or concurrent with calculation of the filing fees, please amend this application as follows.

IN THE CLAIMS

Applicants have attached to this Amendment documents entitled "Amended Claims" and "Marked-Up Copy of Previous Claims". Please amend claims4 as shown in the document entitled "Marked-Up Copy of Claims". Please add new claim 7 as shown in the document entitled "Amended Claims".

REMARKS

Entry and consideration of this Preliminary Amendment is respectfully requested prior to or concurrent with calculation of the filing fees. This Preliminary Amendment is being filed to remove the multiple dependent claims to avoid the surcharge.

Examination on the merits is awaited.

Respectfully submitted,

SMITH, GAMBRELL & RUSSELL, LLP

By:_

Dennis C. Rodgers, Reg. No. 32,936 1850 M Street, N.W., Suite 800 Washington, D.C. 20036 Telephone: (202) 659-2811 Fax: (202) 263-4329

March 19, 2002

MARKED UP COPY OF CLAIMS

4. (Amended) The method in accordance with claim 2 [or 3] characterized in that the control system 2 may be turned off through said error signal.

AMENDED CLAIMS

- 4. (Amended) The method in accordance with claim 2 characterized in that the control system 2 may be turned off through said error signal.
- 7. (New) The method in accordance with claim 3 characterized in that the control system 2 may be turned off through said error signal.

10088233

WO 01/22566

5

10

15

20

25

30

3/p/

JC13 Rec'd PCT/BR00/00105

JC13 Rec'd PCT/PTO 1 9 MAR 2002

Title: "A METHOD FOR CONTROLLING AND PROTECTING ELECTRIC MOTORS,
A SYSTEM FOR CONTROLLING ELECTRIC MOTORS AND AN ELECTRIC
MOTOR SYSTEM"

Disclosure of the invention

The present invention is directed to a method for controlling and protecting electric motors, specially permanent magnet motors electronically actuated by a control system comprising a three-phase inverting bridge, in which it is required to monitor the position of the rotor by using a position detector physically attached to the axle or through the tension induced in the coils by the magnet, in order to correctly control actuation by the control system. The present invention is also directed to a system for controlling electric motors and an electric motor system.

The objective of the present invention is to prevent one or more switches of the three-phase inverting bridge from being actuated at an improper time, what can lead to the generation of high currents which cannot be detected by the current detector, said currents may cause the auto-demagnetization of the rotor magnet, besides causing damages to the switches of said inverting bridge.

Description of the State of the Art

The detection of the rotor position is required for the actuation of permanent magnet motors.

In accordance with the prior art to the present invention, such detection can be accomplished through sensors physically connected to the rotor ("hall", optical type, and the like) or by observing the voltages induced in the motor coils themselves, as described in Brazilian Patent Application PI 8805485, in such a way that the control may correctly select which phases of the motor will be activated every time.

As described in more details below, the control unit, when normally operating, analyzes the input of the position detector and current protection detector, thus activating the respective outputs in accordance with a predetermined table. However, if there is a failure in the position detector, it is likely that one or more switches of the three-phase inverting bridge is unduly activated, the result of which can be the generation of high currents that are not detected by the current detector, thus resulting in the auto-demagnetization of the motor magnet and damages to the switches of the three-phase inverting bridge.

As known, the demagnetization of the magnet makes it difficult to start the

- 2 -

WO 01/22566 PCT/BR00/00105

motor, decreases the output and overheats the motor, being inadmissible in all the cases.

Still according to the prior art to this invention, the following measures to prevent the auto-demagnetization of the motor magnet are adopted: the design of a more robust motor, with an increased magnet thickness, what would increase notably the cost, specially in view of a larger magnet; the installation of a current protection detector in every switch or every phase of the motor, what would not only increase the cost but also the complexity of the system, by virtue of the higher number of detectors and signals for the control to analyze; or the simple elimination of the protection against auto-demagnetization, thus placing the integrity of the motor under the statistical possibility of the occurrence of a failure, what represents a serious risk not only for the system, but also for the image of the manufacturer.

Brief Description and Objects of the Invention

5

10

15

20

25

30

After a number of investigations, it was evidenced that, when normally operating and following the same rotation direction, the sequence where the positions of the rotor are updated in the sensor is always the same. Thus, such sequence can be predetermined, whereby the control unit of the system for controlling an motor could foresee the sequence where the positions of the rotor will be changed. By knowing the speed the motor is rotating at, it is possible to foresee the time when the position of the rotor will be changed.

With these information, the control unit can prevent failures when the motor is actuated, thus assuring the integrity of the rotor magnet and the inverting bridge switches.

In accordance with the teachings of the present invention, the control unit will accept only the position foreseen for the applicable rotation direction as valid, and always at the time expected for the present speed.

Preferably, when determining this time, a tolerance range defining a minimum time and a maximum time, during which a change in the position should take place, should be considered.

The present invention has the advantages, compared to the prior art, that it is not necessary to any oversize the rotor magnet, the cost and the complexity of the motor are decreased, and the current protection detector is simplified, besides conferring a greater reliability to the system.

Such advantages are attained through a method for controlling and protecting

5

10

15

20

25

30

electric motors provided with a rotor, specially permanent magnet motors electronically actuated by a control system comprising a three-phase inverting bridge, characterized by comprising the step of counting a first period of time, during which said rotor should be between an original position and the next position, and the step of counting a second period of time that follows said the first period of time, during which said rotor should pass through said next position.

The present invention is also expressed as a system for controlling an electric motor provided with a rotor, specially a permanent magnet motor, comprising a threephase inverted bridge and characterized by being additionally comprised of a microcontroller capable of analyzing the positions of the rotor as a function of the time, associated with a counter capable of carrying out the step of counting a first period of time, during which said rotor should be between an original position and the next position, and the step of counting a second period of time subsequent said first period of time, during which said rotor should pass through said next position, as well as an electric motor system comprising a control system, an electric motor electronically actuated by the control system; and characterized by being additionally compriseds of a microcontroller capable of analyzing the positions of the rotor as a function of the time, associated with a counter capable of carrying out the step of counting a first period of time, during which said rotor should be between an original position and the next position, and the step of counting a second period of time that follows said first period of time, during which said rotor should pass through said next position.

Brief Description of the Drawings

The present invention will be described below in more details with reference to the accompanying drawings, wherein:

Figure 1 represents a block diagram of an electric motor system electronically actuated by a control system;

Figure 2 is a schematic representation of a three-phase inverting bridge;

Figure 3 is a three-phase inverting bridge actuation table; and

Figure 4 is a generic flowchart of a method for controlling and protecting electric motors that incorporates the teachings of this invention.

Detailed Description of the Invention

With reference to Figures 1 and 2, an electric motor system 1 is electronically actuated by a control system 2 comprising a rectifying bridge 3 basically, a capacitive

-4-

WO 01/22566 PCT/BR00/00105

filter 4, a three-phase inverting bridge 5, a three-phase motor provided with a permanent magnet rotor 10, a control unit 11, position detectors SA, SB and SC, and a current protection detector PI.

As known in the state of the art, the control unit 11 is responsible for the monitoring of the position detectors SA, SB and SC and the current protection detector PI in order to excite, through the respective outputs, the switches T1 through T6 of the three-phase inverting bridge 5 at a suitable time in accordance with the table illustrated in Figure 3.

5

10

15

20

25

30

Thus, in response to the command of the control unit 11, the three-phase inverting bridge 5 will also apply a current to the coils of the motor 10 at the right time.

As already mentioned, in the event there is any failure in the position detectors SA, SB and SC, it is possible that one or more switches T1 through T6 of the three-phase inverting bridge 5 is not properly activated, what can generate high currents that are not detected by the current protection detector PI, resulting in the auto-demagnetization of the motor and damages to the switches T1 through T6 of the three-phase inverting bridge 5.

In accordance with the teachings of the present invention, the control system 2 also includes a microcontroller (not-shown) capable of analyzing the positions of the rotor as a function of the time, associated with a counter capable of carrying out successive steps of time counting. As known in the art, such counter may be an internal component of said microcontroller.

Said counter is set to zero whenever there is a change in the position of the rotor of the electric motor 10, the counting of a first period of time is started, during which period the rotor should be between a position and another one. Later on, the counting of a second period of time is started, during which time the rotor should pass through the next position.

In a three-phase motor with two poles there are six basic positions P1 through P6 of the rotor as shown in Figure 3, which positions should be successively reached by the rotor during a respective second period of time.

If the rotor passes through one of the positions during said first period of time, what would be too early, or after said second period of time has elapsed, what would be too late, it means that there has been some error, and then said microcontroller turns off the control system 2 in order to prevent further damages, thus preserving

WO 01/22566 PCT/BR00/00105

the integrity of the rotor magnet and the switches of the three-phase inverting bridge.

If the rotor pass through the correct position during said second period of time, the microcontroller will issue an output updating signal and restart the counter, preparing same for counting the first and second periods of time corresponding to the next position where the rotor should pass through.

5

10

15

20

Of course, if the rotor, during said second period of time, passes through a position that is not the correct one, it also means that there has been some error, and then said microcontroller turns off the control system 2.

Figure 4 represents a generic flowchart of a method for controlling and protecting electric motors to exemplify the present invention.

In accordance with the specific teachings of this invention, said second period of time should include a tolerance for the moment the rotor passes through a given position. As an example, in a three-phase motor with two poles rotating at 3,000 rpm, the rotor takes 20 ms to complete one turn, and thus it shall consume 3.3 ms for passing through each position.

In order to come up with said tolerance, said second period of time measured by the counter should include a first head range of 1.65 ms (x/2) and a second tail range of 6.6 ms (2x) beyond the regular 3.3 ms, what represents a tolerance of x-50% and x+100%.

After a preferred example of realization has been described, it should be understood that the scope of the present invention encompasses other possible variations, being limited only by the contents of the appended claims including the possible equivalents.

5

10

15

20

25

30

CLAIMS

- 1- A method for controlling and protecting electric motors (10) provided with a rotor, specially permanent magnet motors electronically actuated by a control system (2) comprising a three-phase inverting bridge (5), characterized by comprising a step of counting a first period of time, during which said rotor should be between an original position and the next position and a step of counting a second period of time that follows said first period of time, during which said rotor should pass through said next position.
- 2- The method in accordance with claim 1, characterized by comprising an additional step of issuing an error signal if said rotor passes through said next position before or after said second period of time, or an output updating signal to restart a counter in the event the rotor passes through said next position during said second period of time.
- 3- The method in accordance with claim 2, characterized by comprising an additional step of issuing an error signal if said rotor passes, during said second period of time, through a position other than the one that follows said original position.
- 4- The method in accordance with claim 2 or 3 characterized in that the control system 2 may be turned off through said error signal.
- 5- A control system (2) for an electric motor (10) provided with a rotor, specially a permanent magnet motor, comprising a three-phase inverting bridge (5) and characterized by being additionally comprised of a microcontroller capable of analyzing the positions of the rotor as a function of the time, associated with a counter capable of carrying out the step of counting a first period of time, during which said rotor should be between an original position and the next position, and the step of counting a second period of time that follows said first period of time, during which said rotor should pass through said next position.
- 6- An electric motor system 1 comprising a control system (2), an electric motor (10) electronically actuated by the control system 2, and characterized by being additionally comprised of a microcontroller, capable of analyzing the positions of the rotor as a function of the time, associated with a counter capable of carrying out the step of counting a first period of time, during which said rotor should be between an original position and the next position, and the step of counting a second

- 7 -

WO 01/22566 PCT/BR00/00105

period of time that follows said first period of time, during which said rotor should pass through said next position.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 29 March 2001 (29.03.2001)

PCT

(10) International Publication Number WO 01/22566 A1

(51) International Patent Classification7:

H02P 6/12

- (21) International Application Number: PCT/BR00/00105
- (22) International Filing Date:

20 September 2000 (20.09.2000)

(25) Filing Language:

English

(26) Publication Language:

English

- (30) Priority Data:
 PI 9904253-3 20 September 1999 (20.09.1999) BR
- (71) Applicant (for all designated States except US): EM-PRESA BRASILEIRA DE COMPRESSORES S.A.
 EMBRACO [BR/BR]; Rua Rui Barbosa, 1020, CEP-89210-901 Joinville, SC (BR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): DAINEZ, Paulo,

Sergio [BR/BR]; Rua Rui Barbosa, 1431, Apt. 302, Bloco I, Joinville, SC (BR). VON DOKONAL, Luiz [BR/BR]; Rua Visconde de Mauá, 241, Joinville, SC (BR). SCHWARZ, Marcos, Guilherme [BR/BR]; Rua General Osório, 257, Joinville, SC (BR).


- (74) Agent: DANNEMANN, SIEMSEN, BIGLER & IPANEMA MOREIRA; Rua Marquês de Olinda, 70, Botafogo, CEP-22251-040 Rio de Janeiro, RJ (BR).
- (81) Designated States (national): CN, JP, KR, SG, TR, US.
- (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

[Continued on next page]


(54) Title: A METHOD FOR CONTROLLING AND PROTECTING ELECTRIC MOTORS, A SYSTEM FOR CONTROLLING ELECTRIC MOTORS AND AN ELECTRIC MOTOR SYSTEM




(57) Abstract: A method for controlling and protecting electric motors (10) provided with a rotor, specially permanent magnet motors electronically actuated by a control system (2) comprising a three-phase inverting bridge (5), characterized by being comprised of the step of counting a first period of time, during which said rotor should be between an original position and the next position, and the step of counting a second period of time that follows said first period of time, during which said rotor should pass through said next position. The present invention is also expressed as a control system (2) for an electric motor (10) provided with a rotor, specially a permanent magnet motor, comprising a three-phase inverting bridge (5) and characterized by being additionally comprised of a microcontroller capable of analyzing the positions of the rotor as a function of the time, associated with a counter capable of carrying out the step of counting a first period of time, during which said rotor should be between an original position and the next position, and the stage of counting a second period of time that follows said first period of time, during which said rotor should pass through said next position, as well as an electric motor (1) comprising the control system (2).

WO 01/22566 A1

PCT/BR00/00105






2/3

	INLET				OUTLET					
ROSITON	POSITION DETECTOR CURRENT			,	SWITC	H AC	ruati(NC		
	SA	SB	SC		T6'	T5'	T4'	T3'	T2'	T1'
P1	1	0	1	0	0	0	1	0	0	1
P2	1	0	0	0	1	0	0	0	0	1
P3	1	1	0	0	1	0	0	7	0	0
P4	0	1	0	0	0	0	0	1	1	0
P5	0	1	1	0	0	1	0	0	1	0
P6	0	0	* 1	0	0	1	1	0	0	0
X	X	X	X	1	0	0	0	0	0	0

Fig. 3

3/3



Transmissing Distignt Patents
Sole & Tom Threntons
Convention & Non-convention
PCT & Non-PCT

PCT & Non-PCT
This form cannot be amended, attered
or changed after it is sugged
(For use axify for inventors who
(if understand the English language.)

Declaration and Power of Attorney. United States Patent Application

As a below named inventor, I hereby declare that:

My residence, post office address and entirenship are as stated below next to my name.

Note is a subject of the subject matter which is claimed and for which a patent is sought on the inventor plucal names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled.

(check one) a is attached hereto.	plication No. 10/088, 233 Man	rch 19,2002 and (if applicable)	
was amended on	and filed or	20.	2000:
was filed as PCT In	ternational Application NoPCT/I	BROO/00105 unSeptember 20,	and (if applicable)
was amended under	PCT Arnole 34 on		
tracknowledge the duty to disclose interf	Dation Auton is inspectal to become outs.	, including the claims, as amended by any ar as defined in Title 37, Code of Federal Regu	7.5
I hereby claim foreign priorny benefits u	inder Title 35. United States Code, §1196	a)-(d) or \$365(b) of any foreign and PCT ap- cast one country other than the United States icate or PCT international application having	plication(s) for patent or inventor's of America listed in this Declaration.
I have also identified below any loreign application(s) on which priority is claim	application for parent of meetings a serior		
Foreign/PCT Application No.	Country	Filing Date	Priority Clauned? (yes/no)
Poreign/PC1 Application No.			
PI 9904253-3	Brazil	September 20,1999	yes
United States of America listed in this L	tion in the manner provided by the first phility as defined in Title 37, Code of Fed	f any United States application and PCT inte tter of each of the claims of this application saragraph of Title 35, United States Code, 5, and Regulations, \$1.56 which became available	12 Lacknowledge the duty to disclose
U.S. Application No.	Filing Date	Status (patented/pending/abandoned?)	
기를 된 열 없는 그는 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그			- ·
		4 (1944)	
I hereby claim priority benefits under T	nie 35 United State's Code §1 19(e) of an	y U.S. provisional application(s) listed below	v.
U.S. Provisional Application No.	Filing.Date		•
Weilacher (20,531), Herbert M: Hanega (32,263), Dennis C. Rodgers (32,936), Nelson (48,119).	Mary A. Monrebello (33,021). Enc J. Ha	sact all business in the Patent and Trademar erick F. Calvetti (28,557), J. Rodgers Lunsfo mson (44,738), Patrick R. Delaney (45,338)	Brandon S. Boss (46,567), and Brett L
Send all correspondence to SMITH, G	AMBRELL & RUSSELL LLP, 1850 M	Street, N.W. (Surte 800), Washington, D.C.	20036. All lacsimiles may be sent to (20
263-4329. Direct all phone calls to (40	7),033*2011- 3		
I hereby declare that all statements mad be true; and further that these statement both, under Section 1001 of Title 18 of	le herein of my dwn knowledge are true i is were made with the knowledge that wi the United States Cede and that such wi	and that all statements made on information ilful false statements and the like so made a liful false statements may joopardize the val	and belief are believed to re punishable by fine or imprisonment, or Idity of the application or any patent issue
thereon.			
Full name of sole or first inven	tor PAILO SERGIO DATI	NE2	Citizenship: Brazilian
			•
Post office address: Rua Ru	E Barbosa, 1431 - al	pt9 302	
Doinvi	lle, SC, Brazil	509	4/02
Signature Perla Di	He, SC, Brazil t	Date: -06/1	
수 없는 사람이 없는 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그	TITZ VON DO	KONAL	Citizenship: Brazilian
Post office address: Rua V	isconde de Mauá, 24	10.1	
Johny	time, SC, Brazil	DKY	2/02
Signature = Link		Date Ob/O	+107
Names of the ho			,

Citizenship: Brazilian

SCHWARZ

Residence (city: state, country): Joinville, SC.
Post office address: Rua General Osorio, 2
Joinville, SC., Brazil Signature: c Citizenship: Full name of fourth joint inventor, if any: Residence (city, state, country): Post office address: Date: Signature: Citizenship: Full name of fifth joint inventor, if any: Residence (city, state, country): Post office address: Date: Signature Citizenship: Full name of sixth joint inventor, if any; Residence (city, state, country): Post office address: Date: Signature Citizenship: Full name of seventh joint inventor, if any: Residence (city, state; country). Post office address: Date Signature: Citizenship: Full name of eighth joint inventor, if any: Residence (city, state, country): Post office address: Date Signature:

MARCOS GUILHERME

Full name of third joint inventor, if any: